



Key Features

- Ductless System
- Quiet and efficient operation
- Advanced electronic control system
- Liquid bottle probe
- Energy saving mode
- Alarm capabilities
- Flexible installation
- 55°F temperature differential

Features

At WhisperKOOL, we have redesigned the housing for the Platinum series split system evaporators. While the internal components have proven to be reliable and effective, we have designed new housing systems for improved installation and accessibility. The previous design was a little challenging in terms of mounting and accessing the components for installation. It required the removal of the top or side panel. When racking was installed around the unit, it was difficult to gain access for service or maintenance.

Our new design makes the units easier to install by gaining access to system from the front of the unit where we have installed removable grills. This greatly improves the ability to install the system and access it for maintenance. Please note that the dimensions have changed slightly. Review the specification section when planning your install to account for the dimensional change. At WhisperKOOL, we believe in the goal of continuous improvement in everything we do in order to enhance the customer's experience.

Specifications

Model	4000	8000
Cellar Size	1000 cu. ft.	2000 cu. ft.
BTUh @ 55°	4715	6006
CFM	270	278
Dimensions	Evaporator: 20.56"W x 15.5"H x 16"D • Condenser: 11.5"W x 9.91"H x 16"D	
Refrigerant	R-134a	
HP	1/2	1/2+
Voltage Rating	115V or 230V - 20 amp dedicated circuit required	
Weight	Evaporator: 56lbs • Condenser: 56lbs	Evaporator: 56lbs • Condenser: 66lbs
AMPS (starting/running)	Evaporator: 2/1 • Condenser: 15/10	Evaporator: 2/1 • Condenser: 18/9
dBA	Evaporator: 54 • Condenser: 65	Evaporator: 54 • Condenser: 65
Insulated Line Set	1/2" Suction • 1/4" Liquid	1/2" Suction • 1/4" Liquid
Drainline	1/2" Condensate	
Installation	Evaporator is installed in the cellar, condenser is installed up to 100 line feet away and with the installation specifications found in the owners manual. Allow for adequate airflow.	
Thermostat	Digital Control Display	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Warranty	2 year parts and labor	

Optional Accessories

Exterior Condenser Housing, Cold Weather Start Kit

