

26" BUILT-IN AIR CONDITIONERS

THROUGH-THE-WALL DESIGN FOR FLUSH-MOUNT APPLICATIONS
COOLING-ONLY OR ELECTRIC HEAT OR HEAT PUMP MODELS



Specifications for:

Cooling Models:

PBC092E00CB
PBC122E00CB
PBC093E00CB
PBC123E00CB

Electric Heat Models:

PBE093E35CB
PBE123E35CB

Heat Pump Models:

PBH092E12CB
PBH093E35CB
PBH113E35CB

NEW IMAGE TO COME

OFFERING TOTAL COMFORT WITH EASY-TO-USE CONTROLS!

- ELECTRONIC TOUCH PAD WITH REMOTE CONTROL
- HIGH ENERGY EFFICIENCY WITH MODELS UP TO 9.8 EER saving you money when compared to lower EER models.
- EASILY REMOVABLE CONDENSER TOP that allows for quick and complete cleaning of outdoor coils. This access for cleaning the outdoor coil enables easy removal of dirt and debris to help lengthen the life of the compressor and other system sealed components. Remove six easy access screws and let the cleaning begin!
- EASY ACCESS SLIDE OUT FILTER has a permanent polypropylene filter mesh that is easy to remove and clean.
- ACCESSORY WALL SLEEVE: PBWS01A is a solid-sided, heavily insulated metal sleeve. It includes a stamped aluminum exterior grille with a weather-seal rear enclosure for installation without the chassis. The sleeve has a solid bottom for complete weather-tight installation. An optional PBWMFC can be used when a more permanent weather seal is needed for sleeves installed without the chassis.
- 100% FULL FACTORY RUN TEST on all units for high reliability and dependability. Units start the first time — every time!
- QUIET OPERATION. Designed with guest comfort in mind — providing reliable, quiet operation for years to come.

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operational cost, or energy efficiency rating that is available from your retailer.

| Amana® brand Model | Cooling Only Models | | | | Electric Heat Models | | Heat Pump Models | | |
|-----------------------------------|---------------------|-------------|---------------|-----------------|----------------------|-----------------|------------------|----------------|-----------------|
| | PBC092E00CB | PBC122E00CB | PBC093E00CB | PBC123E00CB | PBE093E35CB | PBE123E35CB | PBH092E12CB | PBH093E35CB | PBH113E35CB |
| General Features: | | | | | | | | | |
| Voltage | 115 | 115 | 230 / 208 | 230 / 208 | 230 / 208 | 230 / 208 | 115 | 230 / 208 | 230 / 208 |
| Approx. chassis weight | 75 lbs | 77 lbs | 75 lbs | 77 lbs | 77 lbs | 79 lbs | 79 lbs | 79 lbs | 81 lbs |
| Approx. shipping weight | 88 lbs | 90 lbs | 88 lbs | 90 lbs | 90 lbs | 98 lbs | 92 lbs | 92 lbs | 95 lbs |
| Cooling: | | | | | | | | | |
| Capacity / BTUH | 9,200 | 11,800 | 9,200 / 8,900 | 11,800 / 11,400 | 9,200 / 8,900 | 11,800 / 11,400 | 9,000 | 9,000 / 8,700 | 11,500 / 11,100 |
| Amps | 8.6 | 11.6 | 4.4 / 4.7 | 5.6 / 6.0 | 4.4 / 4.7 | 5.6 / 6.0 | 8.8 | 4.5 / 4.8 | 5.7 / 6.2 |
| Watts | 940 | 1,260 | 940 / 910 | 1,200 / 1,160 | 940 / 910 | 1,200 / 1,160 | 960 | 960 / 930 | 1,220 / 1,180 |
| CFM | 275 | 275 | 275 | 275 | 265 | 265 | 265 | 265 | 265 |
| E.E.R. | 9.8 | 9.4 | 9.8 / 9.8 | 9.8 / 9.8 | 9.8 / 9.8 | 9.8 / 9.8 | 9.4 | 9.4 / 9.4 | 9.4 / 9.4 |
| Dehumidification - pts/hr | 2.5 | 3.4 | 2.5 | 3.4 | 2.5 | 3.4 | 2.5 | 2.5 | 3.4 |
| Electric Heat: | | | | | | | | | |
| Capacity / BTUH | n/a | n/a | n/a | n/a | 11,000 / 9,000 | 11,000 / 9,000 | 3,900 | 11,000 / 9,000 | 11,000 / 9,000 |
| Amps | n/a | n/a | n/a | n/a | 15.0 / 14.0 | 15.0 / 14.0 | 11.0 | 15.0 / 14.0 | 15.0 / 14.0 |
| Watts | n/a | n/a | n/a | n/a | 3,500 / 2,900 | 3,500 / 2,900 | 1,150 | 3,500 / 2,900 | 3,500 / 2,900 |
| Heat Pump: (Reverse cycle) | | | | | | | | | |
| Capacity / BTUH | n/a | n/a | n/a | n/a | n/a | n/a | 8,500 | 8,500 / 8,200 | 11,000 / 10,700 |
| Amps | n/a | n/a | n/a | n/a | n/a | n/a | 7.7 | 4.0 / 4.2 | 5.2 / 5.6 |
| Watts | n/a | n/a | n/a | n/a | n/a | n/a | 860 | 860 / 830 | 1,195 / 1,160 |
| C.O.P | n/a | n/a | n/a | n/a | n/a | n/a | 2.9 | 2.9 / 2.9 | 2.7 / 2.7 |
| Thermostatic drain valve | n/a | n/a | n/a | n/a | Yes | Yes | Yes | Yes | Yes |
| Electrical Data: | | | | | | | | | |
| NEMA plug configuration | 5-15P | 5-15P | 6-15P | 6-15P | 6-20P | 6-20P | 5-15P | 6-20P | 6-20P |
| Plug type | Parallel | Parallel | Tandem | Tandem | Perpendicular | Perpendicular | Parallel | Perpendicular | Perpendicular |
| Power cord length | 8.0' w/LCDI | 8.0' w/LCDI | 6.0' w/LCDI | 6.0' w/LCDI | 6.0' w/LCDI | 6.0' w/LCDI | 8.0' w/LCDI | 6.0' w/LCDI | 6.0' w/LCDI |

Note: Units ship without the optional PBWS01A wall sleeve and require a solid-side sleeve for field installation. If installing into existing sleeves, call your Amana brand sales person for compatibility assessment or adapter kits. Damage caused by improper sleeves, or by use of improper grilles, is not covered by the product warranty.

Features: (all models)

| | |
|------------------------|--|
| Agency Approval | U.L. (Underwriters Laboratory) listed; USA and Canada |
| Chassis Type | Slide-out for easy installation and service accessibility |
| Fan speeds: | 2 speeds: High & Low |
| Energy Saver | Yes - (Cooling only - Auto fan operation) |
| Fan ONLY | Yes - High Speed |
| Exhaust CFM | 30 |
| Discharge air | Top discharge with 4-way adjustable air throw |
| Slide-out-filter | Top Pull-out Polypropylene - Permanent filter that is washable |
| Condensate drain spout | Yes - external drain spout on the PBWS01A optional wall sleeve |


Optional Accessories:

| | |
|-----------|---|
| PBWS01A | Insulated metal sleeve for installation of 26" Built-In Air Conditioners; solid side and solid bottom with weather board and stamped aluminum grille. |
| PBAGK01TB | Architectural grille kit for use with PBWS01A sleeve and 26" Built-In Air conditioners in beige. |
| PBAGK01SB | Architectural grille kit for use with PBWS01A sleeve and 26" Built-In Air conditioners in custom colors |
| PBWMFC01A | An insulated metal cover for use when PBWS01A is installed without 26" Built-In Air Conditioner |
| PBFAK01A | Sleeve adapter kit; converts Fedders BSAOOC & Friedrich WSC 27" wall sleeves for use with Amana 26" Built-In Air Conditioners |

Dimensions:

| | Height | Width | Depth |
|------------------------|-----------|--|----------------------------------|
| Chassis Dimensions: | 15 5/8" | 26.0" | 16 7/8" |
| With chassis installed | | Depth with chassis installed and room front cover attached = 21 7/8" | |
| Sleeve Cut-outs: | 15 13/16" | 26 3/16" | Maximum wall thickness = 16 3/8" |

Plug Type:



1-Year Entire Unit Limited Warranty*

5-Year Sealed System Limited Warranty*

1-Year Entire Unit and 5-Year Sealed System Components. Goodman Company L.P. will repair or replace any factory defective part or sealed system leak caused by a defective part. See product warranty for complete details.

*Complete warranty details available from your local dealer or at www.amana-ptac.com



Call us at **800-647-2982** for complete details.

CB-TTW4 05-14