




DCA 3500T AIR COOLED - NON WATER HEATING DEHUMIDIFIER

DCA 3500TWH WATER HEATING ASSIST DEHUMIDIFIER

PERFORMANCE



Performance	82DB / 50% R.H.	82DB / 60% R.H.	Notes
Moisture Removal, LB/HR	37.0	47.7	1
Net Sensible Cooling, MBH	54.6	48.4	2
Net Reheat, MBH	61.4	73.4	3
Water Heating, MBH (Water Heating Models Only)	116.4	122.0	4

Notes:

1. Reheat mode assuming 1050 BTU/lb.
2. Cooling mode with remote condenser at 95F.
3. Defined as sum of latent and compressor input. Use dehumidifier for supplemental heat only.
4. Assuming 85F entering water temperature.
5. For conditions and data not shown contact the factory.

CAUTIONS: The reheat capacity rating includes latent recovery and heat of compression. It is recommended that dehumidifiers be used for supplemental heat only. The cooling capacity is based on an ambient temperature of 95°F. As outside conditions vary, so will the performance of the dehumidifier. Ratings are subject to change without notice.

DESIGN SPECIFICATIONS

Electrical	208/230V
Phase/Hz	1/60
Compressor B.T.U.	93,000
Compressor RLA	(2) x 19.9
Compressor LRA	(2) x 137
Blower Motor H.P.	2
Blower Motor FLA	10
Unit FLA	51.7
Maximum Fuse Size	70
Minimum Circuit Amp.	56.6
Operating kW	9.35

CFM.....	3500
External Static Pressure	0.50" H ₂ O
Refrigerant.....	R-407C (Factory Charged 45 lbs.)
Compressor Type.....	Tandem Scroll
Filter (Quantity: 4)	20" x 25" x 1" Fiberglass
Drain Connection	1" Bar Drain
DCA 3500T Weight	950 lbs.
DCA 3500TWH Weight	1200 lbs.
Liquid Inlet [inches O.D.] (up to 50') ¹	0.625
Hot Gas Outlet [inches O.D.] (up to 50') ¹	1.125
Water Inlet [inches O.D.].....	1.375
Water Outlet [inches O.D.].....	1.375
Water Flow G.P.M. ²	16.0
Pressure Drop (Ft. WC) ²	9.0

¹ Over 50ft contact factory

² Water Flow data based on 50% RH + Return Air 82°F and Pool Water at 85°F

STANDARD FEATURES

- MET Laboratory Safety Listed To UL 1995
- 3 Year Parts Warranty
- Single Refrigeration Circuit
- Tandem Scroll Compressors
- Powder Coated, Galvannealed Steel Cabinet
- Low Ambient Head Pressure Control



- Remote Condenser Ready
- Rifle Tube Refrigeration Coils
- TEFC Blower Motor
- Stainless Steel Condensate Drain Pan
- Standard Microprocessor Control System (WH Models Only)
- ElectroFin Coated Coils

OPTIONAL FEATURES

- Right Side Component Service Access
- Top or Bottom Discharge (Not Field Convertible)
- Extended Surface Filters 2" & 4"
- Outdoor Installation Package
- Outdoor Make Up Air Assembly with Damper & Filter
- External Static Upgrade
- Water Cooled Condenser For Water Heating Or A/C Available
- Motorized Evaporator Bypass Damper
- Remote Ready Delete
- Defrost Timer Package
- Control Options
- Space Heating Options Available
- Other Options Available