

## Dri-Eaz Airmover Specifications

Name	Sahara Pro X3	Sahara HD	Sahara E	Ace	Vortex Axial Fan	Jet CXV
Model #	F351	F352	F350	F259	F174-BLU	F367
Height	18.8" / 47.8 cm	18.8" / 47.8 cm	18.8" / 47.8 cm	24" / 61 cm	19.2" / 49 cm	25.9" / 65.8 cm
Width	17" / 43.2 cm	17" / 43.2 cm	17" / 43.2 cm	20.3" / 51.5 cm	18.7" / 48 cm	25.9" / 65.8 cm
Depth	18.3" / 46.5 cm	18.3" / 46.5 cm	18.3" / 46.5 cm	19" / 48.3 cm	15.7" / 40 cm	18.9" / 48 cm
Weight	27 lb / 12 kg	36 lb / 16 kg	24 lb / 11 kg	33 lb / 15 kg	35 lb / 16 kg	35 lb / 16 kg
Motor	0.33 hp	1.0 hp	0.25 hp	0.25 hp	1.0 hp	0.25 hp
Motor Speeds	3-speed	3-speed	1-speed	2-speed	1-speed	3-speed
Max Rated CFM	2700	3500	2250	2250	2041	3200
Tested Velocity or CFM*	2071 FT/MIN (631 M/MIN) Velocity	3206 FT/MIN (977 M/MIN) Velocity	2042 FT/MIN (622 M/MIN) Velocity	1881 FT/MIN (3196 M/MIN) Velocity	1820 FT/MIN (3092 M/MIN) Velocity	n/a
CFM/AMP** Tested CFM Per 15-AMP Circuit**	235 CFM/AMP 2817 CFM/ Circuit	145 CFM/AMP 1454 CFM/ Circuit	129 CFM/AMP 926 CFM/ Circuit	1254 CFM/AMP 15,048 CFM/ Circuit	n/a 1820 CFM/ Circuit	n/a
Static Pressure	1.28" / 3.25 cm	2.75" / 7 cm	1.24" / 3.15 cm	n/a	3.2" / 8.1 cm	n/a
Power	4.0 amps	10 amps	7.2 amps	1.5 amps	7.4 amps	1.5, 2, 3 amps amps
Positions	Three (0°, 45° and 90°)	Three (0°, 45° and 90°)	Three (0°, 45° and 90°)	Seven	One	Two
Stackable	Yes	Yes	Yes	Yes	Yes	Yes
Carpet Clamp	Optional	Optional	Optional	n/a	n/a	n/a
Housing	Rotomolded	Rotomolded	Rotomolded	n/a	n/a	Rotomolded
UL/C-UL Listed	Yes	Yes	Yes	Yes	Yes	ETL tested to UL & CSA standards

\* Velocity or CFM is listed, depending on the performance metric most relevant for a specific airmover's application.

\*\* CFM/AMP or Circuit is critical when maximizing airflow on a drying job.