



# SUBMITTAL AQV24VBE High Wall 24,000 Btu/h Heat Pump

Job Name	Location		
Purchaser	Engineer		
Submitted to	Reference <input type="checkbox"/>	Approval <input type="checkbox"/>	Construction <input type="checkbox"/>
Unit Designation	Schedule #		

Specifications	
<b>General</b>	
Nom Cooling Capacity (Btu/h)	24,000
SEER	15.5
Cool Capacity Range (Btu/h)	6,500 to 27,000
Nom Heating Capacity (Btu/h)	27,000
HSPF	7.8
Heating COP	2.8
Heat Capacity Range (Btu/h)	5,800 to 33,000
Refrigerant Type	R410A
De-Hum (Pints/Hr)	14.4
Power Voltage	208/230v-1Ph-60Hz
Breaker Size	25A
RLA Cooling/Heating (Amps)	12.0/13.0A
Controls	Wireless
<b>Indoor Unit AQV24VBE</b>	
Airflow-High Speed (CFM)	530
Fan Speeds	Turbo-High-Med-Low
Noise Level Low/High (Db)	30/41
Width (Inches)	42"
Height (Inches)	11 3/4"
Total Depth (Inches)	8 5/8"
Weight (lbs)	28.6
Condensate Connection Ø	11/16" OD
<b>Outdoor Unit AQV24VBEK</b>	
Outdoor Noise Level (Db)	55
Width (Inches)	34 5/8"
Height (Inches)	25 1/8"
Total Depth (Inches)	12 1/4"
Weight (lbs)	112.2
<b>Line Sets</b>	
Size	1/4 & 5/8"
Max Line Set Length inc	98 ft
Max Vertical Separation of	49ft
Charged with R410A for	25ft (51.1oz R410A)
Addl R410A charge required	0.15oz/ft over 25ft
<b>Certifications</b>	
Safety	ETL & ETLc
Performance	ARI Certified
ARI Certification reference #	
<b>Warranty</b>	
	5 Years Compressor
	3 Years Parts
	120 Days ltd labor
<b>Options</b>	
	25 or 50ft Line Sets
	Condensate Pumps
	Condenser Brackets



### Construction

Indoor Unit shall be made from UL94 V0 HIPS  
The Outdoor unit shall be galvanized steel with a baked on powder coated finish for durability

### Heat Exchangers

The heat exchangers shall be mechanically bonded fin to copper tube. Fins shall be Silver Nano coated

### Refrigerant System

Compressors shall be a hermetically sealed DC Inverter drive rotary type  
Refrigerant shall be R410A.  
Refrigerant flow shall be controlled by Electronic Expansion Valve

### Indoor Fan

The indoor unit fan shall be statically and dynamically balanced. An auto swing louver with dual blades shall direct airflow  
The outdoor unit fan shall be a propeller type

### Controls

The unit shall be operated via a wireless remote  
Control signal shall be a DDC type signal  
Control wiring shall require 16AWG shielded wire  
Unit operating range shall be  
Cooling 14 DegF to 115 DegF  
Heating 5 DegF to 70 DegF

### Air Filtration

MPI Ionizer provides Hydrogen and Oxygen Ions which destroy many viruses, allergens and molds contained in the air stream  
Dual washable Air Filters shall be treated with a Silver Nano coating

Due to Samsung's policy of on-going product development specifications are subject to change without notice

SUB-SAM-VIV24-0209