



## 36" Variable Speed

AVALANCHE-36-VD AVALANCHE-36-1D



5 Year Limited Warranty  
Covers Components



Lifetime Warranty  
Covers Housing

## AVALANCHE-36 SERIES

The COOL-SPACE AVALANCHE-36 Series is the ideal solution to cool workshops, greenhouses, decks and patios. Using just a garden hose and standard electrical outlet, the COOL-SPACE AVALANCHE-36 greatly reduces temperatures in any well ventilated space.

All commercial COOL-SPACE units come standard with edge coated 8 in. thick cooling media for durability and performance, GFI plug for safety, large built-in water reservoirs for up to 10 hours of stand-alone use and a premier 5 year warranty.



### AVALANCHE-36-VD

The AVALANCHE-36-VD portable evaporative cooler has a 36 inch variable speed fan. With up to 9700 cfm it will cool an area of up to 3600 square feet. The 46 gallon built-in water reservoir provides hours of operation without being connected to a water supply.

### AVALANCHE-36-1D

The AVALANCHE-36-1D has a 36 inch single speed fan. With 9500 cfm it will cool up to 2900 square feet.

- Use indoors or outdoors in any well ventilated space
- 3600 sq. ft. of cooling coverage
- Large, built-in, 46 gallon water reservoir for extended use

- Edge coated, 8" thick cooling media for durability, performance and 33% more cooling surface than the standard 6" cooling media



- Ground fault protected electrical cord for additional safety and a cord wrap for easy storage
- Swivel, locking casters for easy maneuvering
- Low water shut-off to extend pump longevity
- Tough, UV resistant, durable roto molded polyethylene housing
- Drain plug and flush valve for water removal
- Conveniently located reservoir cap allows easy water treatment access
- Quiet - comparable to light rainfall

💧 Fill Up 🔌 Plug In ❄️ Cool Down

## AVALANCHE-36-VD

CS6-36-VD



<b>Power Supply</b>	110V/1ph/15A minimum branch circuit
<b>Fan Amperage</b>	6.5 A
<b>Fan Motor</b>	High efficiency, totally enclosed .75hp/110V/60Hz, Variable Speed
<b>Fan Size</b>	36"
<b>Airflow</b>	6400 - 9700 cfm
<b>Cooling Media</b>	8" thick, high efficiency, cross corrugated, angle fluted formulated cellulose treated with a thermosetting resin for strength and to prevent growth of algae
<b>Water Supply</b>	Garden hose connection or portable supply tank. Water level regulated by a float valve. Maximum pressure 120 psi
<b>Water Reservoir</b>	Internal 46 gallon capacity
<b>Unit Dimensions</b>	62.5" wide x 30" deep x 70.5" high
<b>Shipping Weight</b>	270 lbs

## AVALANCHE-36-1D

CS6-36-1D



<b>Power Supply</b>	110V/1ph/15A minimum branch circuit
<b>Fan Amperage</b>	6.5 A
<b>Fan Motor</b>	High efficiency, totally enclosed .5hp/110V/60Hz, Single Speed
<b>Fan Size</b>	36"
<b>Airflow</b>	9700 cfm
<b>Cooling Media</b>	8" thick, high efficiency, cross corrugated, angle fluted formulated cellulose treated with a thermosetting resin for strength and to prevent growth of algae
<b>Water Supply</b>	Garden hose connection or portable supply tank. Water level regulated by a float valve. Maximum pressure 120 psi
<b>Water Reservoir</b>	Internal 46 gallon capacity
<b>Unit Dimensions</b>	62.5" wide x 30" deep x 70.5" high
<b>Unit Weight</b>	270 lbs



5 Year Limited Warranty  
Covers Components



Lifetime Warranty  
Covers Housing