▶ ULTRA SERIES ULTRAMD33





THIS IN-WALL DEHUMIDIFIER
FEATURES A SLIM PROFILE TO
MOUNT BETWEEN INTERIOR
STUDS. THE ULTRAMD33*
IS DESIGNED TO CONTROL
MOISTURE INCLUDING IN
MULTI-FAMILY APPLICATIONS.

PERFORMANCE

Water Removal	33 Pints / 4.125 Gallons
Efficiency	4.25 Pints/kWh
Energy Factor	2.0 L/kWh
Blower	155 CFM @ 0.0" WG
Operating Temperature	49°F Min., 95°F Max.
Sizing	Up to 1,200 Sq. Ft. / 12,000 Cu. Ft.

ELECTRICAL


Power	324 watts @ 80°F and 60% RH	
Supply Voltage	120 VAC - 1 phase - 60 Hz	
Current Draw	2.8 amps	
Power Cord	10', 115 VAC, Ground or Hard-Wired	
Circuit Requirement	15 Amps	Plug Type B (USA, MEX, CAN, JPN)

SPECIFICATIONS

Sound Rating	46 dBA
Drain Connection	3/4" O.D.
Drain Hose	10' Condensate Hose (3/4" ID)
Refrigerant	R134A, 10 oz.
Unit Dimensions	14.1875"W x 30"H x 5.75"D
Unit Weight	39 lbs.

SHIPPING

Shipping Dimensions	20"W x 37"H x 11"D
Shipping Weight	57 lbs.
Pallet Quantity	8 per pallet
UPC Number	859029004717
Shipping Options	UPS or LTL



Specifications are subject to change without notice. Performance is based on pints / gallons per day @80°F/60%RH. Sizing is based on 10 foot ceiling height.

* The Santa Fe UltraMD33 was previously known as the Ultra Aire MD33.

FEATURES

MODEL 4035900

- + Designed for quiet operation
- + Washable air filter
- + Ability to be hardwired into existing electrical or directly plugged into a 110v outlet
- + Designed to drain into a hub-drain or plumbing line
- + Internally mounted digital dehumidistat









BUILT TO LAST. BUILT TO PERFORM.

ACCESSORIES

ORDERING INFORMATION

FILTRATION



WASHABLE FILTER

- + For large particle filtration
- + Easy to clean every 1-2 months
- + Simple to remove and replace

INSTALLATION



SURFACE MOUNT KIT

- + Slim profile
- + Easy installation
- + Ideal for masonry or CMU block wall applications or when through-the-wall installation is not available
- + Powder-coated metal provides polished look to blend into any environment



2X4 WALL MOUNT BEZEL KIT

- + Slim profile
- + Easy installation
- + Ideal for applications with a 2x4 cavity without having to cut a hole in both sides of the drywall
- + Powder-coated metal provides polished look to blend into any environment



REAR PANEL KIT

- + Easy installation
- Ideal for 2x4 cavity applications that require covering the back of the dehumidifier or to conceal gaps in drywall
- + Powder-coated metal attaches to rear of dehumidifier providing a polished look to blend into any environment

PARTS

4036923	Power Board	4038144
4038072	Control Board	
4037714	Filter	4038001
4037585	Blower	4037916
4036848	Temperature /	4035235-08
	RH Sensor	4035235-01
4037996	Hose Clamp	4038145

4038144	Diffuser with Filter and
	Sound Dampening Insulation
4038001	3/4" Crush Resistant Hose (10')
4037916	Tamper Resistant Screws
4035235-08	Compressor Capacitor
4035235-01	Blower Capacitor
4038145	Defrost Probe Kit

PART NO. ITEM

4037714	Washable	Filter

4039155 Washable Filter, 6-Pack

PART NO. ITEM

4037766 Surface Mount Kit

PART NO. ITEM

4037767 2x4 Wall Mount Bezel Kit

PART NO. ITEM

4037768 Rear Panel Kit

The Santa Fe team is available Monday - Friday, 8 am - 5 pm CT.

We want to hear from you, so don't hesitate to reach out.

Need help with a warranty claim? Contact us at 800-533-7533.

Contact Customer Service at orders@thermastor.com.

SANTA-FE-PRODUCTS.COM