



Key Features

- Liquid-temperature-measuring Bottle Probe
- Advanced digital controller
- Dynamic airflow
- Coated evaporator coil
- Front or rear power
- Single piece mounting bracket
- Durable finish

Features

The next generation in specialty cooling systems. The SC Series embodies the latest and greatest system design technologies in an all-new housing design. Developed upon feedback directly from customers and installers, the unit incorporates a variety of high end componentry at an affordable price point. The SC Series is a direct replacement for one of the most well known cellar cooling units, the XLT. Just like the series it replaces, the units come in 5 models that effectively cool a 300 to 2000 cu. ft. properly insulated environment. Designed for simple through-the-wall installation, the unit fits between standard wall studs and a single piece mounting bracket eliminates the need for a support shelf. The SC has a 30°F temperature differential. In order to keep your cellar at 55°F, the condenser intake temperature should not exceed 85°F. This makes interior installation ideal for SC series units.

Specifications

Model	2000i	3000i	4000i	6000i	8000i
Cellar Size	300 cu. ft.*	650 cu. ft.*	1000 cu. ft.*	1500 cu. ft.*	2000 cu. ft.*
BTUh @ 55°	1453	2049	2253	4009	4241
CFM	120	131	145	220	374
Dimensions	14.25"W x 15.75"H x 17.5"D			14.25"W x 22.56"H x 21.64"D	
Refrigerant	R-134a				
HP	1/8	1/6	1/6	1/2	1/2
Voltage Rating	115V (20-amp dedicated circuit required); 230V (subject to availability)				
Weight (lbs)	65	67	67	104	104
Amps (running)	2.7	4.9	4.9	10.3	10.3
dBA (Evaporator/Condenser)	60 / 60	60 / 60	60 / 60	65 / 65	65 / 65
Drainline	3/8" ID clear plastic tubing				
Installation	Through-the-wall, partially ducted				
Thermostat	Digital control display, liquid-temperature-measuring bottle probe				
Temp. Delta	30°F temperature differential (maintains proper cellar temperature when intake temperature does not exceed 85°F)				
Outside Venting (Not recommended)	Can be done if the outside temperature does not exceed 85°F, the optional external grille cover is required.				
Ducting Options	Exhaust air can be ducted using the optional ducting kit				
Warranty	Two-year limited warranty (parts and labor) / Five-year limited warranty (compressor)				

*Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Optional Accessories

Exhaust ducting kit, exterior housing

