



Key Features

- Ductless system
- Quiet and efficient operation
- Advanced electronic control system
- Liquid-temperature-measuring bottle probe
- Flexible installation
- 55°F temperature differential
- Standard and 24V thermostat options available

Features

At WhisperKOOL, we have redesigned the housing for the Platinum series split system evaporators. While the internal components have proven to be reliable and effective, the previous design was challenging in terms of mounting and accessing the components for installation. It required the removal of the top or side panel. When racking was installed around the unit, it was difficult to gain access for service or maintenance.

Our new design makes the units easier to install by gaining access to system from the front of the unit where we have installed removable grilles. This greatly improves the ability to install the system and access it for maintenance. Please note that the dimensions have changed slightly. Review the specification section when planning your install to account for the dimensional change. At WhisperKOOL, we believe in the goal of continuous improvement in everything we do in order to enhance the customer's experience.

NOTE: The Platinum Split system must be installed by a qualified HVAC-R technician. Failure to have the system installed by a qualified technician will void the warranty.

Specifications

Model	4000	8000
Cellar Size	1000 cu. ft.*	2000 cu. ft.*
BTUh @ 90°F air entering condenser coil	3650	5211
CFM	270	270
Dimensions	Evaporator: 20.5"W x 15.5"H x 16.1"D • Condenser: 12"W x 13.5"H x 18"D	
Refrigerant	R-134a	
HP	1/3++	1/2+
Voltage Rating	115V (20-amp dedicated circuit required); 230V (subject to availability)	
Weight	Evaporator: 56lbs • Condenser: 56lbs	Evaporator: 56lbs • Condenser: 66lbs
AMPS (starting/running)	Evaporator: 2/1 • Condenser: 32/7.2	Evaporator: 2/1 • Condenser: 48/9.5
Insulated Line Set	1/2" Suction • 1/4" Liquid	1/2" or 5/8" Suction (refer to chart) • 1/4" Liquid
Drainline	1/2" ID clear plastic tubing	
Installation	Evaporator is installed in the cellar, condenser is installed up to 100 line feet away and with the installation specifications found in the owners manual. Allow for adequate airflow.	
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Warranty	Two-year limited warranty (parts and labor)	

*Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Optional Accessories

Exterior housing, cold weather start kit, 24V thermostat conversion kit, condenser coil coating

