FRIGIDAIRE.

Home Comfort

FFHP123SS2



FFHP123WS2 Indoor





FFHP123CS2 Outdoor

Signature Features

Quick Cool & Quick Warm

When you need to cool down quickly or warm up faster, use the quick cool/warm mode to speed up the fan.

Effortless™ Temperature Control

Our air conditioners maintain the preset room temperature, so you will remain comfortable at all times.

Programmable 24-Hour On/Off Timer

Customize times to fit your schedule for immediate comfort when you get home. The built-in timer allows you to preset the unit to turn on and off in half-hour increments.

Sleep Mode

Maximum comfort throughout the evening hours with the added benefit of energy savings. With Sleep Mode, the temperature gradually increases a few degrees over the evening.

Ductless Mini-Split Air Conditioner/Heat Pump

Product Dimensions Evaporator (Indoor) Model

 Height
 11-3/8"

 Width
 33-5/16"

 Depth
 8-1/4"

Product Dimensions Condenser (Outdoor) Model

 Height
 23-5/16"

 Width
 33-7/16"

 Depth
 12-5/8"

More Easy-To-Use Features

Multi-Speed Fan

Features three different fan speeds, for more cooling flexibility.

Effortless™ Restart

Automatically resumes operating at its previous settings when power is restored to your unit.

Effortless™ Clean Filter

Our antibacterial filter reduces bacteria, room odors and other airborne particles for a healthier, more comfortable environment.

Ready-Select® Controls

Easily select options with the touch of a button.

Electronic Controls

Allow you to set the comfort level to your preference, while a convenient temperature readout displays the set temperature.




ENERGY STAR®

Performance	BTUs
Cool	12,000
Heat	13,000


FRIGIDAIRE.

Model Numbers	
Set Model Number	FFHP123SS2
Indoor Unit Part Number	FFHP123WS2
Outdoor Unit Part Number ¹	FFHP123CS2
Performance	
BTU (Cool)	12,000
BTU (Heat Pump)	13,000
Cooling Area (Sq. Ft.)	550
SEER (Air Conditioner)	22
HSPF (Heat Pump)	10.1
Inverter Technology	Yes
СОР	3.40
Electrical	
Volts	230V/208V
Min Circuit Ampacity	9 A
Maximum Circuit Breaker	15 A
Rated Watts (Cool)	960
Rated Watts (Heat)	1,100
Features	
Controls	Ready-Select® Controls
Fan Speeds (Cool/Fan/Heat)	4/3/4
Low Voltage Start-Up	Yes
Turbo Fan	Yes
Auto Fan	Yes
Energy Saver	
Sleep Mode	Yes
24-Hour On/Off Timer	Yes
24-Hour On/Off Timer Remote Control	Yes Full-Function
Remote Control	Full-Function
Remote Control Air CFM (High/Med/Low) Indoor	Full-Function 400/288/241/171
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.)	Full-Function 400/288/241/171 Swing/Manual
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width)	Full-Function 400/288/241/171 Swing/Manual Bottom
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh Slide-Out
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low)	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (45)39/35/29
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (45)39/35/29 54
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor Warranty ²	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (45)39/35/29 54
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor Warranty² Included Accessories	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (45)39/35/29 54 Yes
Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor Warranty² Included Accessories Drain Kit (Outdoor Unit)	Full-Function 400/288/241/171 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (45)39/35/29 54 Yes





FFHP123WS21 Indoor



NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.



Product Dimensions	
Indoor -	
A-Height	11-3/8"
B-Width	33-5/16"
C-Depth	8-1/4"
Outdoor -	
A-Height	23-5/16"
B-Width	33-7/16"
C-Depth	12-5/8"

¹Illustration may not represent actual model.

All refrigeration and electrical work must be performed by a certified and licensed refrigeration technician for parts warranty validation. Insulated line sets and control wires are required and available for Frigidaire split systems in 25 ft. length. Each line set is equipped with flare nuts on both ends. Each system requires one line set for each indoor unit installed.

Accessories information available on the web at **frigidaire.com**

Ductless Mini-Split System Air Conditioner/Heat Pump Submittal Sheet


FRIGIDAIRE

FFHP123SS2

Job:	Reference:	Construction:
Location:	Approval:	Unit Number:
Engineer:	Date:	Drawing Number:
Submitted to:	Submitted by:	


Power	
Min Circuit Ampacity	9 A
Maximum Circuit Breaker	15 A
Capacities	
Cooling	12,000 BTU
Cooling Watts	960 W
Min/Max Cooling	3,100 Btu/13,000 Btu
Heatpump Capacity (BTU)	13,000 BTU
HSPF	10.1
Outdoor Sound Rating	54 dB (A)
SEER	22
EER	12.5
Low Ambient Cooling	0 - 115°F
Low Ambient Heating	-5 - 75°F
Voltage/Frequency	230V/208V/60Hz
Dehumidification	3.0 PT/H

Indoor Unit	FFHP123WS2
Dimensions (H x W x D)	11-3/8" x 33-5/16" x 8-1/4"
Max. Wall Thickness	18"
Sound Rating	(45) 39/35/29
Net Weight	25 lb
Shipping Weight	29 lb
Fan Motor Load	.09 A
Number of Fan Speeds	4
Fan Type	Cross flow
RPM at High Speed (cool)	1,400 RPM
Coil Type	aluminum fin & copper tube
Fin Type	coated fin
Pipe Type	copper internal thread
Fin Rows (FPI)	2
Tube Diameter	7mm (5/16")
Drain Connection Size	16mm (5/8")
Compressor	
Compressor Type	Twin Rotary
Compressory Control	DC Inverter
Compressor Load	6.6 A
Locked Rotor Amps	



¹Illustration may not represent actual model.

Outdoor Unit	FFHP123CS2
Dimensions (H x W x D)	23-5/16" x 33-7/16" x 12-5/8"
Sound Rating	54 dB (A)
Net Weight	94 lb
Shipping Weight	101 lb
Fan Motor Load	.36 A
Drive Type	inverter
CFM (high)	1,176
Fan Type	axial flow
Number of Speeds	DC
RPM	900
Coil Type	aluminum fin & copper tube
Fin Type	coated fin
Pipe Type	copper internal thread
Fin Rows (FPI)	2
Tube Size	9.52 mm (3/8")
Features	
Controls	microprocessor
Remote Control	lcd wireless
Temperature Control	61-86°F (16-30°C)
Timer	24 hr
Air Louvers	2 pieces
Horizontal	manual
Vertical	swing
Low Voltage Restart	built-in
Self-Diagnosis	yes
Air Filter	washable, anti-mold
Refrigerant System	
Refrigerant	R410A
Ounces	47.62
Lineset	25 ft
Maximum Height	33 ft
Maximum Line Length	66 ft
Discharge Vapor Line (od)	6 mm (1/4")
Suction (od)	12.7 mm (1/2")
Operating Range	
Indoor Air Cooling Intake Temp Range	>= 62°F
Indoor Air Heating Intake Temp Range	<= 90°F
Outdoor Air Cooling Intake Temp Range	0~115°F
Outdoor Air Heating Intake Temp Range	-5~75°F



FFHP123CS21 Outdoor



FRIGIDAIRE.