

INVERTER
WALL-MOUNTED
HEAT PUMP SYSTEM
18 SEER2, UP TO 9.0 HSPF2

Goodman
Air Conditioning & Heating

eSeries



Features and Benefits

- Swing compressor
- Inverter technology
 - Ideal comfort
 - Energy efficiency & savings
- Flexible installation
- Sleek design - floating dual panel with curved side edges
- Powerful operation:
 - Once activated, this features will engage the indoor fan motor to run at a maximum speed for 20 minutes. The turbo airflow enables the desired temperature to be achieved faster.
- ECO+:
 - Once activated, set temperature will be adjusted automatically to an eco-friendly level while limited the maximum power consumption.
- Sleep mode:
 - Pressing the sleep button activates sleep mode. This function prevents excessive cooling/heating for a pleasant sleep.
- 2 levels of filters to support indoor air quality:
 - Titanium Apatite Filter
 - Catechin filter
- Direct control via the handheld controller (included)

Thank goodness for **Goodman**.®

Heat Pump Specifications



FTXNG09/12A



FTXNG18A



RXNG09/12A



RXNG18A

Class			09	12	18
Model Name	Indoor		FTXNG09AXVJU	FTXNG12AXVJU	FTXNG18AXVJU
	Outdoor		RXNG09AXVJU	RXNG12AXVJU	RXNG18AXVJU
Rated Cooling Capacity (Min ~ Max)		Btu/hr	8,800 (4,400 - 10,200)	11,000 (4,400 - 13,300)	18,000 (6,700 - 20,000)
		kW	2.57 (1.30 - 3.00)	3.22 (1.30 - 3.90)	5.27 (1.96 - 5.86)
Rated Heating Capacity (Min ~ Max)		Btu/hr	9,400 (4,400 - 13,000)	11,300 (4,400 - 16,400)	17,900 (5,800 - 22,500)
		kW	2.75 (1.30 - 3.80)	3.31 (1.30 - 4.81)	5.24 (1.70 - 6.60)
Rated Power Input	Cooling	W	800	1294	1714
	Heating	W	774	1004	1590
Rated EER2		Btu/hr/W	11.0	8.5	10.5
		W/W	3.22	2.49	3.08
Rated COP		Btu/hr/W	12.15	11.26	11.26
		W/W	3.56	3.30	3.30
SEER2			18.0	18.0	18.0
HSPF2			9.0	9.0	8.5
Power Supply		[V/pH/Hz]		208/230/1/60	
Maximum Piping Length		ft (m)	65-5/8 (20)	65-5/8 (20)	98-1/2 (30)
Maximum Piping Elevation		ft (m)	32-13/16 (10)	32-13/16 (10)	32-13/16 (10)
Chargeless		ft (m)	32-13/16 (10)	32-13/16 (10)	32-13/16 (10)
Piping Connections	Liquid	inch (mm)	1/4 (6.4)	1/4 (6.4)	1/4 (6.4)
	Gas	inch (mm)	3/8 (9.5)	3/8 (9.5)	1/2 (12.7)
Operating range - Cooling		°F (°C)	50 - 114.8 (10 - 46)	50 - 114.8 (10 - 46)	50 - 114.8 (10 - 46)
Operating range - Heating		°F (°C)	5 - 64.4 (-15 - 18)	5 - 64.4 (-15 - 18)	5 - 64.4 (-15 - 18)
Operating range - Ambient Cooling		°F (°C)	5 - 114.8 (-15 - 46)	5 - 114.8 (-15 - 46)	5 - 114.8 (-15 - 46)
Indoor Unit					
Unit Dimension	H	inch (mm)	11-1/3 (288)	11-1/3 (288)	11-11/16 (297)
	W	inch (mm)	30-5/16 (770)	30-5/16 (770)	39-9/16 (990)
	D	inch (mm)	9-3/16 (234)	9-3/16 (234)	10-3/4 (273)
Sound Pressure Level (T/H/M/L/SL)	Cooling	dBA	45/43/36/29/19	48/45/37/31/19	50/48/43/37/33
	Heating		45/42/35/29/25	47/43/36/30/26	49/46/41/36/33
Airflow (T/H/M/L/SL)	Cooling	CFM	466/431/322/249/142	473/436/316/247/132	754/716/605/467/395
	Heating		466/402/322/249/219	473/412/316/247/210	754/716/605/467/395
Unit weight		lbs (kg)	20.3 (9.2)	21.4 (9.7)	31 (14)
Outdoor Unit					
Unit Dimension	H	inch (mm)	21-11/16 (550)	21-11/16 (550)	27-13/32 (696)
	W	inch (mm)	26-1/2 (675)	26-1/2 (675)	36-5/8 (930)
	D	inch (mm)	11-3/16 (284)	11-3/16 (284)	13-13/16 (351)
Sound Pressure Level (H)	Cooling	dBA	46	48	53
	Heating		48	48	53
Unit weight		lbs (kg)	55 (25)	62 (28)	97 (44)

Remarks:

1. Due to product innovation, all specifications are subjected to change by the manufacturer without prior notice.
2. All units are being tested according to AHRI 210/240 Standard.
3. Nominal cooling capacity are based on the conditions: 80°F (26.7°C) DB / 67°F (19.4°C) WB indoor and 95°F (35°C) DB outdoor.
4. Nominal heating capacity are based on the conditions: 70°F (21.1°C) DB indoor and 47°F (8.3°C) DB / 43°F (6.1°C) WB outdoor.



A DAIKIN BRAND

Air Conditioning & Heating

Our continuing commitment to quality products may mean a change in specifications without notice.