

Quest 132D

Desiccant Dehumidifier

1.877.420.1330
www.QuestHydro.com



Specifications:		
Part Number:	4037900	
Power:	66 KWh/Day	
Supply Voltage:	2 Circuits; 15 Amps, 115VAC each 22 Amps total power consumption	
Capacity:	132 Pints (80°F 60%RH)	
Process Air:	385 CFM Process Airflow (@ 0" ESP) 75 CFM Reactivation Airflow (@ 0"ESP)	
Operating Range:	10°F to 120°F	
Filters:	Process Filter Size: 16" X 20" X 2" Reactivation Filter Size: 12" X 12" X 1"	
Duct Options:	Reactivation Duct: 6" (Start collars included) Connections Process Duct: 8" (Start collars included)	
Warranty:	1 year 100% parts and labor	
Dimensions:		
	Unit	Shipping
Width:	20"	25"
Height:	36"	47"
Depth:	20"	24"
Weight:	105 lbs	125 lbs

Water Removal Rates (Pints/Day)

65 Pints	100°F, 20%
180 Pints	90° F, 90%
150 Pints	80° F, 80%
132 Pints	80° F, 60% (AHAM)
130 Pints	70° F, 80%
120 Pints	70° F, 60%
120 Pints	60° F, 80%
115 Pints	60° F, 60%
125 Pints	50° F, 80%
100 Pints	50° F, 60%
30 Pints	10° F, 80%

