

Quest PowerDry 385D Pro



Desiccant Dehumidifier

PowerDry 385D Pro Specifications

Part Number	4029110
Power	2 Circuits; 11Amps, 115VAC each 22 Amps total power consumption
Kilowatts	2.5 (63 KWh/Day)
Capacity (24hr)	115 Pints (80 °F 60%RH)
Blower:	385 CFM Process Airflow @ 0" ESP 75 CFM Reactivation Airflow @ 0"ESP
Temperature Range	-10 °F to 140 °F*
Filters:	Process Filter Size: 16" X 20" X 2" Reactivation Filter Size: 12" X 12" X 1"
Duct Connections	Process inlet: 12" Flex-Duct (optional) Process Outlet: 10" Lay Flat collar (optional) Reactivation Inlet: 6" Flex-Duct (optional) Reactivation Outlet: 6" Flex-Duct (required)
Warranty	1 Year Parts and Labor

*Low temperature performance is dependent on reactivation air source. Supplying warmer reactivation air will significantly increase water removal.

Dimensions

	Unit	Shipping
Width	24-1/4"	27-1/2"
Height	40"	45-1/2"
Depth	21-3/8"	22"
Weight	105 Lbs.	130 Lbs.

Accessories and Replacement Filters

4029498	MERV 7 Filter
4029521	Flex Duct 12"x25'
4029252	Lay Flat Duct 10" Round x 250'
4029501	MERV 11 Filter
4029519	Flex Duct 6"x25'
4026315	12" x 12" x 2" MERV 7 Filter



Quest PowerDry
385D Pro

ETL Listed



Features:

- Wide operating range for dehumidification
- Superior low dew point operation
- 115 Pints/Day @ AHAM (15 Gallons)
- 22 Amps total power consumption
- Factory installed 115VAC power cords (2 required @ 15 Amps each)
- Vertical or horizontal operation
- Unlimited ducting possibilities
- Process airflow 385 cfm
- Reactivation airflow 75 cfm



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 03/17



Therma-Stor^{LLC}
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com