## Port-A-Cool Cyclone™ 2000





Centrifugal Air Supply,

The Two-Speed Motor

Cools 500 sq. ft.

- Adjustable Louvers
- Quieter Running Centrifugal Fan
  - Smaller Footprint
- Lowers temperatures up to 30 degrees F
- Energy efficient 2.5 amps for pump and motor
- Water level sight tube and sump drain
- 3/4" garden hose connection for longer running
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability—near maintenance-free operation
- Shipped completely assembled—ready to operate out of the box
- UL Listed (electric models) in U.S. and Canada

## Port-A-Cool Cyclone™ 3000

Speeds	Two
Air Delivery CFM	1,600 / 2,000
Total Amps	2.5
Water reservoir	10 gallons
Dimensions	31"h x 24"w x 25"d
Unit weight	61 lbs.
Shipping weight	72 lbs.
Box Size	37"h x 25"w x 27"d
Cooling Capacity	500 sq.

STOCK NUMBER PACCYC02 (BLACK)
STOCK NUMBER PACCYC02A (SIENNA)